

# Debian

## clamav daemon auf Debian System überwachen

```
md /usr/local/src/clamwatch
```

```
wget http://mikecathey.com/code/clamwatch/clamwatch.txt
```

Ausführbar machen:

```
chmod +x clamwatch.txt
```

```
mv clamwatch.txt clamwatch.pl
```

Pfad in der clamwatch.pl anpassen:

```
____SNIP____  
my $Socket = $options{s} || "/var/run/clamd.ctl";  
my $log = $options{l} || 0;  
my $ip = "127.0.0.1";  
my $timeout = $options{t} || 15;  
my $lockFile = $options{L} || "/var/lock/subsys/clamd";.pl  
____SNIP____
```

```
my $Socket = $options{s} || "/var/run/clamav/clamd.ctl";  
my $log = $options{l} || 0;  
my $ip = "127.0.0.1";  
my $timeout = $options{t} || 15;  
my $lockFile = $options{L} || "/var/lock/clamd/clamd";
```

```
md /var/lock/clamd
```

```
cp /usr/local/clamwatch/clamwatch.pl /usr/local/bin/clamwatch.pl
```

```
crontab -e
```

```
*/1 * * * * root    /usr/local/bin/clamwatch.pl -q && ( /usr/bin/killall -9 clamd; rm  
-fr /var/amavis/clamd; /etc/init.d/clamav-daemon start 2>&1 )
```

Eindeutige ID: #1054

Verfasser: Michael Stender

Letzte Änderung: 2008-03-27 06:24