

Plesk

Debian Clamav installation Plesk 7.5

Clamav:

Install the Debian packages clamav, clamav-daemon and clamav-freshclam.

```
[code]plesk:~# apt-get install clamav clamav-daemon clamav-freshclam[/code]
```

Download and extract qsheff and ripmime tar balls.

```
[code]plesk:~# cd /usr/local/src/
```

```
plesk:/usr/local/src#
```

```
wget http://surfnet.dl.sourceforge.net/sourceforge/qsheff/qsheff-II-2.1-r2.tar.gz
```

```
plesk:/usr/local/src# wget http://www.pldaniels.com/ripmime/ripmime-1.4.0.7.tar.gz
```

```
plesk:/usr/local/src# tar zxvf qsheff-II-2.1-r2.tar.gz
```

```
plesk:/usr/local/src# tar zxvf ripmime-1.4.0.7.tar.gz[/code]
```

Building and installing ripmime is straightforward:

```
[code]plesk:/usr/local/src# cd ripmime-1.4.0.7
```

```
plesk:/usr/local/src/ripmime-1.4.0.7# make
```

```
plesk:/usr/local/src/ripmime-1.4.0.7# make install[/code]
```

Ripmime will now be installed in /usr/local/bin; an appropriate place, and right where

qsheff expects it.

creating symlink of ripmime to /usr/bin/

```
[code]ln -s /usr/local/bin/ripmime /usr/bin/ripmime[/code]
```

Now build and install qsheff:

```
[code]plesk:/usr/local/src# cd qsheff-II-2.1-r2
```

```
plesk:/usr/local/src/qsheff-II-2.1-r2# ./configure
```

```
plesk:/usr/local/src/qsheff-II-2.1-r2# make
```

```
plesk:/usr/local/src/qsheff-II-2.1-r2# /etc/init.d/qmail stop
```

```
plesk:/usr/local/src/qsheff-II-2.1-r2# make install[/code]
```

Now, before starting qmail, we have to fix the clamav path in the qsheff config file.

Edit qsheff.conf:

```
[code]mcedit /usr/local/etc/qsheff-II/qsheff.conf[/code] and change
```

```
[code]VIRUS_PROG = "/usr/local/bin/clamscan --quiet"[/code]
```

to

```
[code]VIRUS_PROG = "/usr/bin/clamscan --quiet"[/code]
```

You will probably want to change

```
[code]enable_blackhole = 0;[/code]
```

to

```
[code]enable_blackhole = 1;[/code]
```

as well.

Continue the installation:

```
[code]mv /var/qmail/bin/qmail-queue /var/qmail/bin/qmail-queue.bak
```

```
plesk:/usr/local/src/qsheff-II-2.1-r2# /usr/local/etc/qsheff-II/install-wrapper.sh
```

```
plesk:/usr/local/src/qsheff-II-2.1-r2# /etc/init.d/qmail start[/code]
```

And everything should be working!

Eindeutige ID: #1027

Verfasser: Michael Stender

Letzte Änderung: 2007-08-08 03:14