

Confixx

Confixx User Interface unter <https://confixx.meinedomain.de> einrichten.

Einfach folgen Code in die httpd.conf einfügen.

ACHTUNG!

Bitte nicht vergessen den Code anzupassen!

```
[size=11][code]## CONFIXX
<Directory "/srv/www/htdocs/confixx/html">
  AllowOverride all
</Directory>
<VirtualHost xxx.xxx.xxx.xxx:80>
  ServerName confixx.meinedomain.de
  #User confixx
  #Group users
  RedirectPermanent / https://confixx.meinedomain.de/
  DocumentRoot /srv/www/htdocs/confixx/html
  php_admin_value safe_mode_exec_dir /srv/www/htdocs/confixx/bin
  php_admin_value upload_tmp_dir /srv/www/htdocs/confixx/tmp
  ScriptAlias /cgi-bin/ /srv/www/htdocs/confixx/html/cgi-bin/
  CustomLog /var/log/httpd/confixx.meinedomain.de_access.log "%h %l %u %t \"%r\"
  %s %b \"%{Referer}i\" \"%{User-agent}i\""
  ErrorLog /var/log/httpd/confixx.meinedomain.de_error.log
  php_admin_value sendmail_path "/usr/sbin/sendmail -t -i -f
webmaster@meinedomain.de"
</VirtualHost>
[/code][size]
```

Dies ist der SSL Eintrag. SSL Zertifikate nicht vergessen zu erstellen. Anleitungen findet man ebefalls hier in den FAQ's.

```
[size=11][code]
NameVirtualHost xxx.xxx.xxx.xxx:443
## SSL CONFIXX
<Directory "/srv/www/htdocs/confixx/html">
  AllowOverride all
</Directory>
<VirtualHost xxx.xxx.xxx.xxx:443>
  ServerName confixx.meinedomain.de
  ServerAlias confixx.*
  #User confixx
  #Group users
  DocumentRoot /srv/www/htdocs/confixx/html
  php_admin_value safe_mode_exec_dir /srv/www/htdocs/confixx/bin
  php_admin_value upload_tmp_dir /srv/www/htdocs/confixx/tmp
  php_admin_value sendmail_path "/usr/sbin/sendmail -t -i -f
webmaster@meinedomain.de"
  ScriptAlias /cgi-bin/ /srv/www/htdocs/confixx/html/cgi-bin/
  CustomLog /var/log/httpd/ssl_confixx.meinedomain.de_access.log "%h %l %u %t
  \"%r\" %s %b \"%{Referer}i\" \"%{User-agent}i\""
[/code]
```

Confixx

```
ErrorLog /var/log/httpd/ssl_confixx.meinedomain.de_error.log
SSLEngine on
SSLCertificateKeyFile /etc/ssl/private/confixx.meinedomain.de.pem
SSLCertificateFile /etc/ssl/certs/confixx.meinedomain.de.pem
SetEnvIf User-Agent ".*MSIE.*" \
    nokeepalive ssl-unclean-shutdown \
    downgrade-1.0 force-response-1.0
<Files ~ "\.(cgi|shtml|phtml|php3?)$" >
SSLOptions +StdEnvVars
</Files>
</VirtualHost>[/code][[/size]
```

Eindeutige ID: #1014

Verfasser: Michael Stender

Letzte Änderung: 2007-08-08 03:02